



**emisión directa**  
direct emission



Downlight empotrable para lámpara halógena dicroica QR-CBC51 y PAR16 12V máx. 50W y para lámpara de halogenuros metálicos HIT 35W.  
Cuerpo realizado en chapa de acero estampado.  
Fijación mediante muelles de hilo de acero.  
15.020/15.320: luminaria prevista para ser alimentada mediante transformador de seguridad de 12V de acuerdo a EN 60.742.  
15.220: luminaria prevista para conectar directamente a la red 220V.  
Casquillo GX5,3 (QR-CBC51).  
Casquillo GX10 (HIT 35W).  
Casquillo GU10 (PAR16).  
Luminaria de Clase II: PAR16 y HIT 35W.  
Luminaria de Clase III: QR-CBC51.

Recessed downlight for 12V 50W (max.) QR-CBC51 and PAR16 dichroic halogen lamp and 35W HIT metal halide lamp.  
Housing made of stamped steel sheet.  
Fixation through means of two steel springs.  
15.020/15.320: luminaire prepared for connection to 12V security transformer according to EN 60.742.  
15.220: luminaire prepared for direct connection to 220V.  
Lamp holder GX5,3 (QR-CBC51).  
Lamp holder GX10 (HIT 35W).  
Lamp holder GU10 (PAR16).  
Class II luminaire: PAR16 and HIT 35W.  
Class III luminaire: QR-CBC51.

REFERENCIAS | REFERENCES

QR-CBC 51 50W	15.020
HIT 35 W	15.120
PAR16 50W	15.220

COLORES | COLOURS

.1 Blanco White	.8 Inox Inox	.9 Gris Metal Metal Grey	.10 Acero Esmerlado Grinding Steel
-----------------------	--------------------	--------------------------------	--

DIBUJO TÉCNICO | TECHNICAL DRAWING

